#### INSITU STABILIZATION of SOILS by INJECTION of HIGH-DENSITY POLYURETHANE: PRINCIPLES AND APPLICATIONS

aka Insitu Soil Stabilization by Injecting Polyurethane or ISSBIP



#### AGENDA

- FUNDAMENTALS
  - GOAL OF PRESENTATION
  - **ISSBIP DEFINITION**
  - ISSBIP TENETS
- OBSERVATIONS
  - ISSBIP: SOIL / POLYMER INTERACTION
  - ISSBIP ADVANTAGES
  - **ISSBIP APPLICATIONS**

#### **AGENDA (continued)**

- CASE STUDY: STABILIZING BRIDGE APPROACHES AND DEPARTURES
- SUMMARY / DISCUSSION

## FUNDAMENTALS



## **GOAL OF PRESENTATION**

Provide essential information on ISSBIP to engineering professionals involved in evaluating insitu soil stabilization alternatives

A process for stabilizing weak and/or poorly compacted soils insitu and leveling structures (including bridge approaches / departures) by injecting a specially-formulated polyurethane into the soils

- ISSBIP Polyurethane Description
  - Low viscosity when introduced into the soil
  - 2-component: Resin & Hardener (1:1 by volume)
  - Exothermic chemical reaction between the two components creates CO2 gas which causes polymer expansion and creates pressure on the surrounding environment
  - Formulated to resist water intrusion into the reaction

- ISSBIP Polyurethane Description
  - Rapid Cure
    - Reaction complete in < 1 minute</li>
    - Can support traffic after 20 minutes
    - Full strength in 24 hours
  - Rigid Structural Polyurethane created as the material cures
  - Installed density range 3 to 20 pcf

- ISSBIP Process Description
  - The heated components are introduced in the impingement gun and forced down the injection tube by air pressure
  - The low viscosity polymer flows easily into the voids and weak zones in the soil mass
  - As the reaction occurs, the expanding polymer compacts the surrounding soils; continued injection yields lift
  - Reaction mass necessary for compaction is achieved by 1) weight of pavement and overlying soil
     2) stabilized mass in the upper elevations by employing a top-down injection pattern

### **ISSBIP TENETS**

- Polymer is placed via an injection tube; "surgically" placed in the strata where stabilization is needed
- Multiple injection tubes are used to promote full coverage throughout the area being stabilized
- Injected substance is a two-component, high-density polyurethane characterized by rapid expansion and large volume increase created by chemical reaction between the components
- Movement is monitored at the surface during the injection process

# **OBSERVATIONS**

11

#### **ISSBIP SOIL / POLYMER INTERACTION**

- Complex Issue
  - Governed by both soil and polymer properties
  - Can be further impacted by adjusting operational parameters (heat and injection pressure)
- Soil Properties density, grain size, porosity, permeability, degree of saturation
- Polymer Properties chemical composition and viscosity
- Operational Parameters injection temperature, injection pressure, shot duration, and shot sequencing

- Aggregate Bases/Subbases and Coarse Sand
  - Polymer Infiltration (binding)
  - Polymer Expansion (compacting)
- Saturated Fine Sands
  - Polymer expansion displaces the water and flowable soils
  - Polyurethane encapsulates the remaining soil and begins to "set up"

- Layers with Silts and Clay Size Particles
  - Polymer infiltrates the weak lenses in these layers
  - Polymer begins to expand encapsulating and compacting the surrounding soils

- Organic Soils
  - When operating in soft soils, the polymer reaction time is accelerated so the polymer spends little time moving laterally
  - The rapid reaction time causes the polyurethane to form a vertical shear wall within the soft soil mass
  - By designing the injection pattern, these walls can be shaped into an interconnected series of confinement cells capable of supporting loads

# PHOTOGRAPHS

#### **Stabilization of Aggregate Subbase**



#### **Excavation Revealing ISSBIP-Stabilized Sand**



## Excavating Native Soil to Expose Crater Repair – Note Polymer Veins



#### Intact Extraction of Stabilized Crater Repair

![](_page_19_Picture_1.jpeg)

#### Forensic Excavation of ISSBIP-Stabilized Peat Deposit

## The constructed structure was removed to expose the injected foam

![](_page_20_Picture_2.jpeg)

#### **ISSBIP ADVANTAGES**

- Fast: can withstand traffic in 20 minutes; achieves full strength within 24 hours
- Reduced Disruption: Minimally Invasive Process
- **Predictable**: Highly Controlled Expansion
- Accuracy: Precision Alignment of Faulted Slabs

#### **ISSBIP ADVANTAGES**

- Lightweight: Provides strength (with minimal weight) to the already distressed soil
- Great utility: a single process which can solve multiple problems
- Permanent: Impervious to Water and Most Chemicals
- Eco-Friendly: Environmentally Benign Material; NSF 61 Certified (can use around potable water)

## **ISSBIP APPLICATIONS**

- Settled or Poorly-supported Transportation Assets
  - Bridge Approaches and Departures
  - Asphalt, Concrete, and Composite Pavements
    - Airfields (runways, taxiways, aprons)
    - Roadways
  - Dips or Faulted Joints
  - Railroads
- Leaking Underground Drainage Systems
- Settled or Poorly-supported Structures

# CASE STUDY

## STABILIZING BRIDGE APPROACHES AND DEPARTURES

#### **CASE STUDY – DESCRIPTION**

- STABILIZING SOILS ON BOTH THE EAST AND WEST ENDS OF A BRIDGE ON US 80 OVERPASSING FM 548
- FORNEY, TEXAS
- JANUARY 2013

#### CASE STUDY – DATA REVIEW

- PHOTOGRAPHS FROM SITE VISIT
- DCP RESULTS
- CONSULTANT'S GEOTECHNICAL REPORT AND SUPPLEMENT

![](_page_27_Picture_0.jpeg)

distressed pavement at interface of asphalt & concrete pavement (Northeast quadrant - looking North from median)

![](_page_28_Picture_0.jpeg)

distressed pavement at interface of asphalt & concrete pavement (Northwest quadrant - looking North from median)

![](_page_29_Picture_0.jpeg)

satisfactory performance at interface of asphalt & concrete pavement (Southwest quadrant - looking South from median)

![](_page_30_Picture_0.jpeg)

settlement at interface of concrete shoulder & asphalt shoulder (Southeast quadrant - looking South from median) PROFILE OF WESTBOUND LANES (US BO @ FM 548)

TRAFFIL

![](_page_31_Figure_1.jpeg)

![](_page_31_Picture_2.jpeg)

![](_page_32_Figure_0.jpeg)

12 TX 01 021 Forney TX DCP Totals												
Depth in	DCP	DCP	DCP	DCP	DCP	DCP	DCP	DCP	DCP	DCP	DCP	DCP
Feet	1	2	3	4	5	6	7	8	9	10	11	12
1.64	17	33	35	7	26	2	30	32	20	15	14	11
1.97	15	58	30	16	24	6	27	24	36	21	20	13
2.30	23	56	38	19	43	8	18	16	16	24	15	10
2.62	21	67	42	15	33	9	16	- 4	17	27	11	7
2.95	15	39	45	8	31	13	7	8	28	25		6
3.28	5	30	39	2	19	16	8	5	31	1 Mar 1993	4	B
3.61	3	34	33	1	37	12	- 4	5	23	-	3	4
3.94	2	38	37	1	34	15	5	65	26	41.0	3	6
4.26	1.1	41	17	2	29	14	1.24	16.4 1	14	- 4	2	11
4.59	and the second	12	13	2	24	9	- 4	-4	11	10.00	1	12
4.92	1 18	17	N N	2	17	5		4	12	3	3	1 B
5.25	2	11	12	1	5	3	11	6	15	5	2	8
5.58	1	2	11	1	5	4	10	5	13	1	15	3
5.90	3	2	8	12		2	8	4	16	5	25	4
6.23	1	3	1	1	3	5	11	4	12	4	28	2
6.56	1	2	2	3	- 48	T	<b>4</b>		15	-4	23	3
6.89	18	4	10.0	2	2	6	11	3	10	15	22	2
7.22	1	-	2	1.1	1	9	14	3	8	55	15	1
7.54	1	3	10	-24	2	2	11	4	6	4	11	4
7.87		2	3	2	85	13	9	1.3	1 · · · · · ·	5	10	4
8.20	1	2	2		3	18	8	6	5	5	16	4
8.53		5	4	1.1	6	15	9	3	-65	7	22	3
8.86	2	7	9	and the second	-55	14	11 N W	3	3	55	21	
9.18	2.2	2	8	1	5		5	4	2	0.00	23	3
9.51	2	2	2	1	3	2	3	- 51		20	31	4
9.84	3	2	2	2	and the second	Sec. Barrie	. 6	5	7	23	36	4
10.17	1	4	5	2	-55	51 M G	1.1.1	- 25	5	17	32	4
10.50	0.5	- 6	3	3	5	3		8	5	14	29	2
10.82	0.5	4	3		3	3	3	6	7	11	35	5
11.15	0,5	2	2	1	5	5	2	5	8	53	26	3
11.48	0.5	5	5		6	9	4	4	5	2.10	25	3.
11.81	0.5	3	17	The second second	6		3	The Party of the P	5	4	42	3
12.14	0.5	6	8	12	5	. 4	2	7	-5	8	59	4
12.46	0.5	3	5	1	6	2	4	3	5	10		5
12.79	0.5	4	11	0.5	4		5	2	3	9		2
13.12	0.5	6	19	0.5	5	1 million (1997)	- A.	4	18	8		1
13.45	0,5	7	18	0.5	3	14		5	16	6		5
13.78	0.5	8	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	0.5	3	1. 3. 1.	- Z	4	11	23		0
14.10	0.5	- 4	9	0.5	2	100 M	3	2	9	- 44		6
14.43	0.5	8	23	2	8	6	3	2	Section .	5		4
14.76	2	5	18	1	6	8	5	3	10			4
15.09	2	3	2	0.5	5	6	7	3	9	6		6
15.42	1. 1. B. 1. 1.	9	2	0.5	5	3	8	2	10	5		9
15.74		8	1	0.5	5	- 4	T	2	12	T		11
16.07	S. 18. 1	19	4	0.5	8	5		1.18	11			13
16.40	5	10	3	0.5	4	1. A. A.	5	0.6	8	5		15
16.73	6	3	3	0.5	3	14	4	0.6	9	8		22

#### The Engineering Group at URETEK USA Inc.

The	Engineering	Group a	t URETEK	USA Inc.

				Th	ne Eng	ineerin	ng Gro	up at L	RETER	USA	Inc.	
17.	06	1. 4	16	1	2	5	16	7	0.6	11	COLUMN STATE	
17.	38	4	5	2	0.5	3	15	16	0.6	12	7	
17.	11	6	7	3	0.5	7	19	7	0.6	13	6	
18.	04	5	7	3	3	6	23	5	1	11	10 Z	
18.	37	T	4	3	3	5	21	3	3	16	-	
18.	70	6	12	3	3	6	27	7	8	19	7	
19.	)2	- 4	20	3	3	- 2	29	14	9	9	8	
19.	35	3	65	4	2	4	36	3	8	12	6	
19.	58	9	4	A.	-5	3	33	5	7	10	9	
20.	01	6	3	- 18	- 1 - T	3	31	Contraction of the	7-	13	7	
20.	34	5	3	1	4	3	29	8	8	11	5	
20.	56	7	3	141	3	2	40	2	6	10	5	
20.	99	5	3	1	3	8	34	5	5	12	.4	
21.	32	2	. 3	Sec. 2	5	5	33	5	7	15	5	
21.	55	9	2		4	4	35	7	9	12	6	
21.	98	11	2	1000	3	- 4	39	8	8	10	10	
22.	30	13	3	and the second	2	4	36	1	7	10	1 B 1	
22.	53	10	2	10	4	3	41	7	4	27	8	
22.	96	21	5	13	7	3	28	16	2	24	6	
23.	29	27	8	6	5	5	33	5	6	31	7	
23.	52	29	-4	32	6	5	29		9	28	2	
23.	94	39	-6	35	6	5	23	5	8	21	6	
24.	27	87		26	7	-4	25	5	9	19	6	
24.	50	91	9	29	7	4	31	6	7	20	5	
24.	33		8	37	7	4	30	7	6	27	5	-
25.	26		10	31	3	7	31	7	7	29	6	
25.	58		9	43	6	6	29	9	8	25	5	
25.	11		10	38	6	9	27	5	6	26	6	
26.	24		8	47	7	9	29	6	6	23	5	
26.	57		11	42	6	8	34	5	5		6	
26.	90		11	48	6	7	37	-4	8		5	
27.	22		10	39	7	5	26	-4	9		5	
27.	55		9	45	7	5	28	6	7		4	
27.	38		11	5 C	9	6	37	5	10		5	
28.	21		13		8	5	41	6	9		6	
28.	54		8		8	8	47	7	10		6	
28.	36		12		9	8	50	8	10		7	
29.	19		15		8	7		7	8		11	
29.	>2		18		9	8		6	11		13	
29.3	35		21		10	1			9		11	
30.	18		19		11			11	12		12	
30.	0		26		13	8		14	13		12	
30.	53		21		11	10		16	17		16	
31.	6		37		15	10		24	14		13	-
31.	19	-	48		17	9		26	16		16	
31.	2		41		21	12		23	14			-
32.	178		46		19	17		38				
32.	-/		59		24	19		33				-

### **CASE STUDY – FINDINGS**

- NON-UNIFORM SLAB SUPPORT FOR THE APPROACH AND DEPARTURE SLABS LED TO SETTLEMENT
- MIGRATION OF FINES FROM THE COMPACTED SOIL ZONE INTO THE STONE ZONE RESULTED IN VOIDING, REDUCTION IN SUPPORT, AND DISTRESSES

### **CASE STUDY – FINDINGS**

- CROSS-SLOPE and LONGITUDINAL SLOPE LED TO RUNOFF COLLECTING IN THE NW QUADRANT (WB DEPARTURE AREA) LEADING TO SATURATED CONDITIONS
- GEOTECHNICAL CONSULTANT FOUND SOIL UNDER WB LANES WAS WEAKER THAN UNDER EB LANES

### **CASE STUDY – FINDINGS**

- GEOTECHNICAL CONSULTANT CONCLUDED THERE WAS CREEP DEFORMATION OF THE EMBANKMENT
- GEOTECHNICAL CONSULTANT SAID IT WAS "DIFFICULT TO ASCRIBE THE ACTUAL CAUSE OF PAVEMENT SETTLEMENT TO ANY ONE FACTOR IN THIS CASE"

### **CASE STUDY – TREATMENT**

- ESTABLISHED A GROUT CURTAIN BETWEEN THE COMPACTED SOIL ZONE AND ROCK ZONE TO PRECLUDE THE MIGRATION OF FINES
- STABILIZED SUPPORT SOILS AND LIFTED SLABS THAT ARE EXHIBITING SETTLEMENT

#### CASE STUDY – TREATMENT

- STABILIZED SOILS SUPPORTING
  PAVEMENTS EXHIBITING DISTRESS
- STABILIZED THE ASPHALT SHOULDER PAVEMENT IN THE NW QUADRANT (WB DEPARTURE AREA) TO REDUCE WATER INFILTRATION INTO THE SUPPORT SOILS

### **CASE STUDY – TREATMENT**

- STABILIZED THE BACKFILL SOILS IN THE RETAINED ZONE OF THE WB LANES (NW and NE QUADRANTS)
- INJECTION DEPTHS/ PATTERN VARIED BASED ON:
  - OBJECTIVE SOUGHT
  - SOIL CONDITIONS
  - MAGNITUDE OF DISTRESS

#### **CASE STUDY – SUMMARY**

- EXECUTED: 11-28 JANUARY 2013 (16 days of actual injection)
- COST OF PROJECT: \$190,349
- 2-YEAR WARRANTY; NO CALL BACKS IN YEAR ONE
- URETEK USA PERSONNEL PERFORMED A ROUTINE "ONE YEAR ANNIVERSARY" INSPECTION ON 4 FEBRUARY 2014

# SUMMARY / DISCUSSION

## **ISSBIP SUMMARY**

- Fixes the problem by stabilizing the soils and increasing the stiffness of the weak layers in order to better support the load
- Fixes the symptom of the problem by lifting the settled pavement or structure to the desired grade
- Completed with minimal downtime

# THANK YOU FOR YOUR TIME

## **MICHIGAN CONTACTS**

- Brian C. Shutts
  - Brian.Shutts@uretekusa.com
  - 269-208-5648 Phone
- Brian Francis
  - brian@geoproductsinc.com
  - 313-300-5888 Phone

- 17 Jul 2012 Geotechnical consultant releases first report on problems with this bridge system (still under warranty)
- 10 Aug 2012 Initial Reconnaissance Visit by URETEK USA Regional Manager
- 15 Aug 2012 Site Visit by URETEK Engineering personnel

- 20 Aug 2012 Initial Remediation Plan and Proposal published by URETEK USA
- 5 Sep 2012 Geotechnical consultant publishes supplemental report
- 23 Sep 2012 Supplement to Remediation Plan published by URETEK USA

![](_page_47_Picture_4.jpeg)

- 20-21 Dec 2012 Dynamic Cone Penetrometer (DCP) testing executed by URETEK USA
- 10 Jan 2013 Site Visit and DCP data review with involved parties
- 11 Jan 2013 Final Remediation Plan and Proposal published by URETEK USA

 11- 28 Jan 2013 – Stabilization of Soils in the Bridge System using ISSBIP

(16 actual injection days within this timeframe)

• 4 Feb 2013 – Inspection by URETEK USA personnel (1-year anniversary)