

MDOT AVL and MDSS Implementation

2014 Michigan Winter Operations Conference
October 28-29, Gaylord

Justin Droste P.E.
OFS Maintenance Operations
drostej@michigan.gov
(517) 636-0518



Operations Field Services Division

Contract Overview

- Awarded Contract to Delcan Technologies September 15th, 2013



- Contract is for 3 years with options for 2 additional years.
- Contract provisions include instrumenting all MDOT Fleet vehicles and Heavy Equipment
- Initial phase/priority is Winter Maintenance Trucks (267 Statewide First Year)
 - Permanent assigned truck
 - 2000 model year or newer
 - Dickey John Control Point spreader controller

Project Goals

Fleet Management

- Accurate mileage and hours reporting
- Ability to monitor current location of vehicles
- Monitor engine and on-board equipment status remotely.

Winter Maintenance Operations

- Accurate reporting of equipment and material usage
- Route monitoring and optimization
- Maintenance Decision Support System (MDSS)



MDOT's Role

Equipment Installation

- MDOT Mechanic installations with vendor support
- Installation inspection and sign off

Support

- Provide support to region staff for common issues/easy fixes
- Coordinate Trainings

Project Management

- Weekly conference calls with vendor
- Ensure contract and Department goals are being met



Vendor's Obligation



One point of contact that is required to:

- Provide working AVL equipment and sensors
- Secure and manage cellular communications from AVL devices (Verizon)
- Ensure necessary information is available to users for both AVL (Delcan) and MDSS (Iteris) websites
- Provide customer support to all users
- Provide training and training materials as needed
- Project management and weekly calls with MDOT



What is MDSS?

- Maintenance Decision Support System
- Weather Forecasting Service Catered to Road Agencies.
- Offers treatment recommendations based on MDOT parameters, weather, and reported maintenance activities.
- AVL units automatically feed MDSS, making recommendations more efficient and real-time.
- Treatment Recommendations not Treatment Absolutes



Data Collection

Info Collected & Transmitted for Winter maintenance

- Air and Pavement Temps
- Blade Up/Down
- Wing/ Plow Usage
- Camera Images
- Weather information (MDSS)
- Maintenance treatment recommendations (MDSS)
- Spreader Information
 - Material Type
 - Application Rate
 - Amount Used



WMTs

Data Transfer Process


**AVL
Provider
(Delcan)**

**MDSS
Provider
(Iteris)**




AVL Website

<http://mdot.delcan.net>



Real-time Data

- Operational
- Engine
- Camera Images






Operations Field Services Division

AVL Website

<http://mdot.delcan.net>



24 Hours of Camera Views




AVL Website

<http://mdot.delcan.net>

- Historical Operations Playback (*Breadcrumbs*)





The screenshot displays the ActiveReports 8 Server web interface within a Windows Internet Explorer browser window. The address bar shows the URL <http://mdot-reports.delcan.net/>. The interface includes a left-hand navigation pane with options like 'File', 'Save', 'Open', 'New', and 'Log Out'. The main content area is titled 'Reports:' and features a filter bar with 'By First Letter', 'By Date', and 'By Models' options. Below this, a section labeled 'AVL-MDOT' contains a grid of report thumbnails. Each thumbnail includes a small icon, a title, and buttons for 'Design', 'Preview', and 'Delete'. The reports listed include: (Excel) Excessive Speed Report, Blade Usage Summary, Blade Usage Summary by Day, Current Vehicles, Daily Vehicle Summary, Geofence Blade Summary By Ga..., Geofence Materials Summary, Geofence Summary by Garage, Hourly Vehicle Summary, Hours Inside Geofence, Idle Exception Report, Last Known Vehicle Data, Material Usage - Daily, Material Usage Report - Hourly, Salting Speeds Compliance - Da..., Salting Speeds Compliance By ..., and Salting Speeds Compliance By ...

Primary Data Reports

- Salting Speed Compliance
- Material Usage
- Blade usage
- Engine Idle
- Geofence Data

Salting Best Practices

Maintenance Advisory

MA 2013-01
August 27, 2013

From Mark Geib, Engineer of Operations Field Services Division

MDOT
Operations Field
Services Division
6333 Lansing Road
Lansing, MI 48917

Questions regarding
this advisory should
be directed to:

Tim Croze
Engineer Manager
Region Support
Phone/517-322-3394
CrozeT@michigan.gov

Justin Droste
Roadway Operations
Engineer
Phone/517-636-0518
DrosteJ@michigan.gov



Best Practices for Applying Deicing Materials

Due to increasing costs and growing environmental concerns regarding the use of deicing materials for winter maintenance operations, it is critical we do everything possible to reduce the use of these materials, while still providing adequate levels of service. A major component of reducing the amount of deicing material required is conducting operations in ways that limit the amount of material that bounces and scatters off the roadway during application. The 2012 MDOT Salt Bounce and Scatter Study concluded that using pre-wet salt and applying deicing materials at slower speeds significantly increases the amount of material that stays on the roadway. Incorporating these practices into MDOT's winter operations program will ensure that as much deicing material as possible remains on the roadway and within the target area (4' on either side of the centerline), where it is most effective.


In order to keep the most deicing material on the roadway during the application process, the following guidelines should be followed (for all MDOT maintenance facilities beginning with the 2013/2014 season):

1. The truck's speed should operate between 20-25 mph while applying deicing material. Every effort should be made to maintain as slow a speed as possible while applying deicing material.

Justified exceptions to this practice may include:

- Peak hours on high-speed roads
- Trucks equipped with technology that limits salt scatter, such as zero-velocity spreaders, slurry generators, etc. Based on results from the 2013 MDOT Salt Bounce and Scatter Study, these advanced systems should not operate faster than 35 mph
- Other circumstances approved by the Region Engineer

2. All salt applied to a roadway should be pre-wet with a liquid chloride product. Rates of pre-wetting should be between 7 to 10 gallons per ton of untreated salt (salt slurry will require more, per manufacturer's recommendations). Salt can be treated at the stockpile, by the truckload, or at the point of application on the truck.



3. For all material delivery systems that allow it, a "boot" sleeve system, which decreases the amount of drop between the spreader and pavement, should be utilized (between 1-6 inches for a loaded truck). This decreases bounce and scatter, but not enough to maintain acceptable efficiencies at speeds above 25 mph.

4. The updated MDOT salt application rate chart should be followed. The chart has been revised to reflect the use of pre-wet salt at slower truck speeds.

MDOT maintenance facility supervisors must submit written plans for their facility to their Associate Region Engineer of Operations by October 1st of each year, detailing intended actions for implementation. Exceptions to these guidelines must be justified in writing on a case-by-case basis (example: per snow route). Consolidated action plans for each region should be submitted to the Engineer of Operations Field Services by October 15th of each year.

http://www.michigan.gov/documents/mdot/MA_2013-01_Best_Practices_for_Applying_Deicing_Materials_432480_7.pdf
Operations Field Services Division

Salting Speeds Compliance By Garage- Daily Custom Enhanced

Garage: Adrian

Dates: 3/1/2014 to 3/15/2014

Date	First Timestamp	Last Timestamp	25mph Compliance	(Data Points)	35mph Compliance	(Data Points)	Total Data Points	Solids Spread (ton)
Name: 04-1475			22.46 %	227	75.81 %	581	776	15.2
3/2/2014	7:39 AM	12:33 PM	40.28 %	143	100.00 %	355	355	8.0
3/5/2014	7:52 AM	8:50 AM	26.92 %	35	78.46 %	102	130	2.1
3/12/2014	6:41 AM	7:04 AM	18.75 %	18	69.79 %	67	96	2.7
3/13/2014	5:24 AM	6:38 AM	15.90 %	31	29.23 %	57	195	2.4
Name: 04-1626			25.17 %	608	95.70 %	2171	2264	60.5
3/1/2014	8:56 PM	11:59 PM	25.19 %	97	100.00 %	385	385	10.1
3/2/2014	12:00 AM	12:00 PM	33.03 %	433	98.40 %	1290	1311	21.2
3/3/2014	5:31 AM	10:48 AM	75.00 %	9	100.00 %	12	12	0.5
3/12/2014	6:01 AM	10:04 PM	12.41 %	69	87.05 %	484	556	28.7
Name: 04-1648			30.12 %	1242	87.00 %	3633	4162	55.6
3/1/2014	8:36 PM	9:13 PM	16.27 %	27	100.00 %	166	166	3.1
3/2/2014	1:38 AM	6:42 AM	50.23 %	429	100.00 %	854	854	9.2
3/3/2014	3:03 AM	10:49 AM	40.68 %	24	91.53 %	54	59	1.1
3/8/2014	9:59 AM	12:54 PM	4.07 %	22	56.19 %	304	541	4.8
3/10/2014	12:19 AM	12:28 AM	25.64 %	10	69.23 %	27	39	0.1
3/12/2014	8:26 AM	11:27 PM	29.17 %	730	89.01 %	2228	2503	37.3
Name: 04-1669			20.14 %	1218	94.88 %	5815	6122	75.3

AVL Data Reports

Material Usage Report

Material Usage

- Data from Spreader Controller
- Consistent Naming

Solid Material	Solid Code
Prewet Salt with Calcium Chloride (8 gal per ton)	WSalCa
Prewet Salt with Salt Brine (8 gal per ton)	WSalBr
Dry Salt for spreader prewet	DSalt
Sand only (dry)	Sand
Salt/Sand Blend	SalSan

Material Usage - Daily

Region: North

Garage: Atlanta; Kalkaska

Date: 3/1/2014 to 3/8/2014

Vehicles: 04-1556; 04-1558; 04-1653; 04-1685; 04-3016; 04-3027; 04-3035; 04-3040; 04-4029; 04-4032; 04-4035

Date	Material	Solids Spread	Season Total
Material: DSALT		533.2 ton	
Region North			
Garage: Atlanta		430.2 ton	
Vehicle: 04-3027		3.4 ton	232.1 ton
3/4/2014 DSALT		3.4 ton	232.1 ton
Vehicle: 04-4032		426.8 ton	451.9 ton
3/1/2014 DSALT		11.4 ton	439.3 ton
3/4/2014 DSALT		414.8 ton	450.6 ton
3/5/2014 DSALT		0.6 ton	451.9 ton
Garage: Kalkaska		103.0 ton	
Vehicle: 04-1556		33.6 ton	501.5 ton
3/1/2014 DSALT		15.9 ton	483.8 ton
3/4/2014 DSALT		17.7 ton	501.5 ton
Vehicle: 04-1558		23.0 ton	323.7 ton
3/1/2014 DSALT		16.6 ton	317.3 ton
3/4/2014 DSALT		6.4 ton	323.7 ton
Vehicle: 04-4029		46.4 ton	538.4 ton
3/1/2014 DSALT		26.2 ton	518.2 ton
3/4/2014 DSALT		20.2 ton	538.4 ton
Material: SALSAN		8.7 ton	
Region North			
Garage: Kalkaska		8.7 ton	
Vehicle: 04-1558		6.8 ton	111.7 ton
3/1/2014 SALSAN		6.8 ton	111.7 ton
Vehicle: 04-4029		1.7 ton	164.7 ton
3/4/2014 SALSAN		1.7 ton	164.7 ton
Vehicle: 04-4035		0.2 ton	366.1 ton
3/4/2014 SALSAN		0.2 ton	366.1 ton

Page 1 of 1

10/20/2014 10:48:25 PM

Blade Usage Summary

Garage: Adrian


Dates: 3/2/2014 to 3/8/2014

Minimum Speed: 4 mph

Name	Blade	Hours Down	First Timestamp	Last Timestamp
04-1491	BELLY	1.9	3/2/2014 1:09 AM	3/4/2014 12:59 AM
04-1491	FRONT	3.4	3/2/2014 1:09 AM	3/5/2014 1:43 AM
04-1491	LEFT	3.4	3/2/2014 1:09 AM	3/5/2014 1:43 AM
04-1491	RIGHT	3.4	3/2/2014 1:09 AM	3/5/2014 1:43 AM
04-1492	BELLY	5.0	3/2/2014 12:00 AM	3/5/2014 12:54 PM
04-1626	BELLY	10.9	3/2/2014 12:03 AM	3/5/2014 2:50 PM
04-1648	BELLY	5.4	3/2/2014 1:17 AM	3/3/2014 1:30 PM
04-1648	RIGHT	3.2	3/2/2014 1:17 AM	3/4/2014 9:10 AM
04-1669	BELLY	6.7	3/2/2014 1:13 AM	3/5/2014 2:26 PM
04-1669	RIGHT	5.6	3/2/2014 1:13 AM	3/3/2014 9:22 AM
04-4025	BELLY	3.6	3/2/2014 2:37 AM	3/5/2014 9:23 AM
04-4025	RIGHT	6.9	3/2/2014 2:37 AM	3/5/2014 1:23 PM

AVL Data Reports

Geofence Reports



- Can create shape boundaries around snow routes, service areas, etc
- Alarm notice option when trucks either enter or leave geofence area.
- Can report time, material used, blading, etc within geofence (*route comparison*)

Geofence Materials Summary


Dates: 3/1/2014 to 3/3/2014

Geofences: (select all)


Material	Start Time	End Time	Hours	Solids Spread
Geofence: Grand Region			0.1	0.2 ton
Vehicle: 04-1574			0.1	0.1 ton
SALT	3/2/2014 11:46 AM	3/2/2014 11:52 AM	0.1	0.1 ton
Vehicle: 04-4034			0.0	0.1 ton
DSALT	3/1/2014 10:24 AM	3/1/2014 10:25 AM	0.0	0.1 ton
Geofence: M-72 West			2.1	8.4 ton
Vehicle: 04-1558			0.8	3.9 ton
DSALT	3/1/2014 3:35 AM	3/1/2014 3:46 AM	0.2	0.6 ton
DSALT	3/1/2014 3:47 AM	3/1/2014 3:59 AM	0.2	1.5 ton
DSALT	3/1/2014 4:03 AM	3/1/2014 4:16 AM	0.2	0.8 ton
DSALT	3/1/2014 4:17 AM	3/1/2014 4:30 AM	0.2	1.0 ton
Vehicle: 04-4029			1.3	4.5 ton
DSALT	3/1/2014 6:39 AM	3/1/2014 6:51 AM	0.2	0.7 ton
DSALT	3/1/2014 7:00 AM	3/1/2014 7:30 AM	0.5	1.9 ton
DSALT	3/1/2014 9:10 AM	3/1/2014 9:47 AM	0.6	1.9 ton
Geofence: US-131 Osceola			13.8	29.4 ton
Vehicle: 04-1546			0.0	0.1 ton
DSALT	3/1/2014 10:31 AM	3/1/2014 10:31 AM	0.0	0.1 ton
Vehicle: 04-1564			2.6	3.6 ton
SALT	3/1/2014 7:24 AM	3/1/2014 7:53 AM	0.5	0.4 ton
SALT	3/1/2014 7:56 AM	3/1/2014 8:10 AM	0.2	0.8 ton

MDSS Website


www.mdot.mxwx.com




- Weather Radar with WMT info.
- RWIS info & Camera images
- MDSS info provided direct to WMT cab (if equipped with monitor).



In-Cab Regional Radar



In-Cab Local Radar



In-Cab Weather Forecast

WEB INTERFACE CHANGE SITE MAIN MENU

Page loaded 2014-02-20 3:50:30 pm EST

Forecast for Red Bud Trail east to M-60 and state line to city limits

Time	Pave Temp (°F)	Air Temp (°F)	Precip Type	Precip Prob (%)	Precip Rate (in/hr)	Snow Cover (%)	Cloud (%)	Wind Speed (mph)	Wind Direction	Wind Gust (mph)
Thu 04:00 PM	40	41	TS	80	-	100	14	SE		
Thu 05:00 PM	42	46	TS	90	-	100	15	SSE		
Thu 06:00 PM	44	50	TS	90	-	100	18	SSE		
Thu 07:00 PM	45	52	TS	80	-	100	19	SSE		
Thu 08:00 PM	45	52	TS	90	-	95	20	S		
Thu 09:00 PM	45	52	RA	90	-	95	22	S		
Thu 10:00 PM	44	50	RA	20	-	90	26	SSW		
Thu 11:00 PM	40	44	RA	10	-	45	26	SW		
Fri 12:00 AM	36	40	RA	10	-	55	26	SW	37	
Fri 01:00 AM	34	37	RA	20	-	65	26	SW	42	
Fri 02:00 AM	35	37	RA	20	-	70	24	SW	40	
Fri 03:00 AM	34	35	RA	20	-	85	24	SW	41	


In-Cab Treatment Recommendations

WEB INTERFACE CHANGE SITE MAIN MENU


Page loaded 2014-02-20 3:50:46 pm EST


Recommended Actions

Selection	Time	Practice: Rate
For US-12, Red Bud Trail east to M-60:		
-	Sat 01:00 AM	Patrol for Trouble Spots (precautionary): -
For US-12, M-60 east to 5 Points Rd:		
-	Fri 05:00 AM	Be Aware of Marginal Precip Risk (precautionary): -
-	Sat 01:00 AM	Patrol for Trouble Spots (precautionary): -
For M-51, State line to City limits:		
-	Sat 01:00 AM	Patrol for Trouble Spots (precautionary): -
For M-51, Niles north to M-152:		
-		Be Aware of Marginal Precip




In-Cab Local Radar





In-Cab Weather Forecast



Page loaded 2014-02-07 1:11:22 pm EST

Recommended Actions

Selection	Time	Practice: Rate
-----------	------	----------------

For US-131, M-43 south to Shaver Rd (non-freeway):

- Sat 04:00 PM Patrol for Trouble Spots (precautionary): -
- Sat 06:53 PM Patrol for Trouble Spots (precautionary): -
- Sat 09:46 PM Patrol for Trouble Spots (precautionary): -

For US-131, M-43 north to M-89:

- Sat 04:00 PM Patrol for Trouble Spots (precautionary): -
- Sat 06:53 PM Patrol for Trouble Spots (precautionary): -
- Sat 08:54 PM Prewet Salt (w/ Boost): 225lbs


For I-94, M-51 to US-131:

- Sat 04:00 PM Patrol for Trouble Spots (precautionary): -
- Sat 06:53 PM Patrol for Trouble Spots (precautionary): -
- Sat 09:02 PM Prewet Salt (w/ Boost): 225lbs
- Sun 12:00 AM Be Aware of Frost Risk (precautionary): -

For I-94, US-131 east to Columbia Ave:

- Sat 04:00 PM Patrol for Trouble Spots (precautionary): -
- Sat 06:53 PM Patrol for Trouble Spots (precautionary): -
- Sat 09:57 PM Prewet Salt (w/ Boost): 50lbs


www.mdot.mxwx.com



- **Snow Route Treatment Recommendations**
*** (Rates per 12' Lane mile, not 24')*
- **Weather analysis/predictions per Snow Route (table and graph)**



MDSS Website Video



Keys to Success

Training, Training, Training

- Installation and Maintenance
- Annual Regional Training
- Annual Administrator Training

Communication: On Going Dialog

- Monthly Region Administrators Meetings
- “Office Hours”: Twice a month open to all users
- Weekly Project Meetings
- Central Document Storage and Access
- Accountability
- Core Team of Testers and Certifiers (4 MDOT Staff)

Year One Accomplishments

- 267 snowplows outfitted
 - 6 regions
 - 30 garages
- Web based AVL & MDSS data access
 - All trucks report data
- Comprehensive trainings
 - 20 equipment installers
 - Over 200 website users
- 130 MDSS routes
- Created several standard reports
- Administrators team created



Year One Experience

AVL and MDSS are game changers

- Proactive vs reactive
- Adapting operational approach based on MDSS
- Incorporating pavement forecasts into pre-storm planning
- Operators are more informed

Takes time to gain trust in MDSS treatment recommendations

Lots of data; What's the most useful?

- Material usage report
- Salting speed compliance reports
- Blade usage
- Supervisors know what their operators are applying

Lessons Learned

- **Get input** from all affected areas of the department before undertaking such a project: fleet, IT, executive management, and garage supervisors, at a minimum. Multiple areas should provide input for the RFP requirements
- **Weekly accountability meetings** with vendor and project management staff help to ensure the agency staff and vendor partners are held accountable for their tasks and deliverables
- To **gain buy-in**, it is necessary to focus more on how these tools can aid with current tasks and reduce manual reporting of labor, equipment and material usage by the operator so they can focus on their maintenance activities
- **Accepting change** takes some people longer than others

Questions

Tim Croze P.E.

1-517-322-3394

crozet@michigan.gov

Justin Droste P.E.

1-517-636-0518

drostej@michigan.gov

MDOT Operations Field Services

6333 Lansing Road

Lansing, MI 48917




MICHIGAN DEPARTMENT OF TRANSPORTATION Automated Vehicle Location (AVL) and Maintenance Decision Support System (MDSS)



AVL Program

MDOT began equipping 270 Winter Maintenance Trucks (WMTs) with AVL equipment in the Fall of 2013. With this technology, MDOT garages and regions are able to better monitor their winter operations. Authorized users are able to see where and when activities are being done, and can view integrated sensory data (such as camera images, plow position, and salt usage). Data can also be easily compiled into executable reports. Shown below is the salting speed compliance report, which relates to efficient use of salt. Similar reports are available for blade life, engine idling, and vehicle usage.



Study	Start Date	End Date	Start Time	End Time	Start Location	End Location	Start Speed	End Speed	Start Salt	End Salt	Start Temp	End Temp	Start Humidity	End Humidity	Start Wind	End Wind	Start Rain	End Rain	Start Snow	End Snow	
1	10/1/2013	10/1/2013	06:00:00	06:00:00	100.000	100.000	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00
2	10/2/2013	10/2/2013	06:00:00	06:00:00	100.000	100.000	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00
3	10/3/2013	10/3/2013	06:00:00	06:00:00	100.000	100.000	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00
4	10/4/2013	10/4/2013	06:00:00	06:00:00	100.000	100.000	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00
5	10/5/2013	10/5/2013	06:00:00	06:00:00	100.000	100.000	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00	10.00

MDSS Program

As an enhancement to the AVL technology, MDOT's contract also includes MDSS service. MDSS is a road weather forecasting service which utilizes specific information about a route (road type, traffic, etc) coupled with MDOT winter operations policies to provide treatment recommendations to operators. With real-time data transmittal from WMT AVL units, MDSS is able to utilize previous operational data to enhance future recommendations.



Recognition

At the 2014 ITS World Congress held in Detroit, MDOT won a "Best of ITS" (ITS America) award for its AVL and MDSS program implementation. While members of the MDOT Operations Field Services Division were present to accept the award, the efforts of many, through contracting and procurement, installation and maintenance by garage employees, and support by region and field services management and personnel, are reasons why MDOT's AVL and MDSS Program is nationally recognized as an innovative program in transportation sustainability.

For Further Information about MDOT's AVL/MDSS Program, contact the Region Support Unit at Operations Field Services.



Operations Field Services Division